




NUMINOS® MOVE S

black / chrome recessed ceiling light, 4000K 55°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. The various downlights and spotlights make a thousand lighting design options possible. Like with the NUMINOS® MOVE S recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



Tekniske data

Item no.	1005363
Antal lysåbninger	1
IP klasse	IP20
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	250mA
IP Tæthedsgard	III
Watt	8.6 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	750 lm
Farvetemperatur	4000 Kelvin
Spredningsvinkel	55 °
Farve	matt black/glossy chrome
CRI	90
UGR ≤	22
LXXBXX-data	L80B50
Højde	6.35 cm
Diameter	10 cm
Nettovægt	0.209 kg

Lyskilde

791831	
Tilbehør	
1006458	LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI
1004789	NUMINOS® S , diffuser Wabe
1004067	LED driver , 15W 250mA DALI
1004788	NUMINOS® S , diffuser Frosted
1004787	NUMINOS® S , diffuser Prisma
1004786	NUMINOS® S , diffuser Ellipse
1006139	Numinos® S Reducing ring , round 160/100mm black
1006454	RF module Casambi for LED bridge driver , single colour
1004058	LED driver , 6.5-10W 250mA
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006140	Numinos® S Reducing ring , round 160/100mm white
1006142	Numinos® S Reducing ring , square 160/100mm white
1004055	LED driver , 6.5-10W 250mA PHASE
1006141	Numinos® S Reducing ring , square 160/100mm black

Bruttovægt	0.248 kg
Indbygningsdybde	8.5 cm
Installations diameter	9 cm
BIG WHITE side	86