



## NUMINOS® MOVE S

white / black recessed ceiling light, 4000K 40°

The NUMINOS light system from SLV perfectly combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® MOVE S recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

Item no.	1005367
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	250 mA
Safety class	III
Wattage	8.6 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	730 lm
Colour temperature	4000 Kelvin
Beam angle	40 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1

## Light Source

791831	
--------	---

### Accessories

1006458	LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI
1004789	NUMINOS® S , diffuser Wabe
1004067	LED driver , 15W 250mA DALI
1004788	NUMINOS® S , diffuser Frosted
1004787	NUMINOS® S , diffuser Prisma
1004786	NUMINOS® S , diffuser Ellipse
1006139	Numinos® S Reducing ring , round 160/100mm black
1006454	RF module Casambi for LED bridge driver , single colour
1004058	LED driver , 6.5-10W 250mA
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006140	Numinos® S Reducing ring , round 160/100mm white
1006142	Numinos® S Reducing ring , square 160/100mm white
1004055	LED driver , 6.5-10W 250mA PHASE
1006141	Numinos® S Reducing ring , square 160/100mm black

Height	6.35 cm
Diameter	10 cm
Net weight	0.22 kg
Gross weight	0.26 kg
Shape of cut-out	round
Installation depth	8.5 cm
Installation diameter	9 cm
BIG WHITE Page	86