


WORKLIGHT

white free-standing lamp. 79W 4000K 80°

As a consistent further development of our WORKLIGHT series, this WORKLIGHT is an office free-standing light for VDU workstations, equipped with state-of-the-art technology and highly efficient, high-output LEDs and, of course, $UGR \leq 19$. Equipped with a motion sensor, the built-in daylight control and the possibility of dimming, it meets all the requirements of today's office lighting. The WORK-LIGHT is ready for direct connection to a 230V mains power supply thanks to its pre-installed driver and supply cable including plug. This light contains integrated LED light bulbs.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1005391 |
| Number of different light outlets | 2 |
| IP Code | IP 20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Mobile |
| Dimmable | Yes |
| Dimming technology | Touch |
| Primary nominal voltage | 200-240V ~50/60Hz |
| Secondary power / voltage | 2000 mA |
| Safety class | I |
| Wattage | 79 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Number of luminaires at LS B16A | 28 |
| Number of luminaires at LS C16A | 28 |
| Level of inrush current | 6.24 A |
| Duration of inrush current | 194 μ s |
| Stroboscopic effect (SVM) | 0 |
| Lumen | 7600 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 80 ° |

Light Source

| | |
|--------|---|
| 916336 |  |
|--------|---|

| | |
|------------------------------|-----------|
| Color | white |
| CRI | 80 |
| UGR \leq | 19 |
| LXXBXX data | L80B10 |
| Service life | 50000 h |
| Risk Group | 0 |
| Length | 69.2 cm |
| Width | 31 cm |
| Height | 195 cm |
| Net weight | 14.546 kg |
| Gross weight | 17.342 kg |
| BIG WHITE Page | 445 |