




## WORKLIGHT

white table lamp. 79W 4000K 80°

As a consistent further development of our WORKLIGHT series, this WORKLIGHT is an office table lamp for screen-based workstations, equipped with state-of-the-art technology and highly efficient, high-output LEDs and, of course, UGR ≤ 19. Equipped with a motion sensor, the built-in daylight control and the possibility of dimming, it meets all the requirements of today's office lighting. The WORKLIGHT is ready for direct connection to a 230V mains power supply thanks to its pre-installed driver and supply cable including plug. This light contains integrated LED light bulbs.



## TECHNICAL DATA

Item no.	1005394
Number of different light outlets	2
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Mobile
Dimmable	Yes
Dimming technology	Touch
Primary nominal voltage	200-240V ~50/60Hz
Secondary power / voltage	2000 mA
Safety class	I
Wattage	79 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	28
Number of luminaires at LS C16A	28
Level of inrush current	6.24 A
Duration of inrush current	194 µs
Stroboscopic effect (SVM)	0
Lumen	7600 lm
Colour temperature	4000 Kelvin
Beam angle	80 °

## Light Source

916336	
--------	---

<b>Color</b>	white
<b>CRI</b>	80
<b>UGR <math>\leq</math></b>	19
<b>LXXBXX data</b>	L80B10
<b>Service life</b>	50000 h
<b>Risk Group</b>	0
<b>Length</b>	69.2 cm
<b>Width</b>	31 cm
<b>Height</b>	120 cm
<b>Net weight</b>	6.413 kg
<b>Gross weight</b>	9.029 kg
<b>BIG WHITE Page</b>	445