




## MILANDOS 4

black recessed ceiling light, 3000K 45°



The MILANDOS recessed ceiling light convinces with its compact design and innovative lighting properties. It shines above all with a high colour reproduction index of over 90 out of 60,000. With a UGR of 16, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends stylishly into any room. The spotlight is also quick and easy to install. When will you test out the benefits of SLV's impressive indoor lights?



### Tekniske data

Item no.	1005408
IP klasse	IP20
IK Vandalklasse	IK02
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	700mA
IP Tæthedegrad	III
Watt	8 W
Omgivelsestemperatur	30 °C
Lumen	520 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	45 °
Farve	matt black/black
CRI	90
UGR ≤	16
LXXBXX-data	L80B50
Længde	13.6 cm
Bredde	5.6 cm
Højde	4.3 cm
Nettovægt	0.231 kg
Bruttovægt	0.286 kg
Indbygnings længde	13 cm

## Lyskilde

1078215	
998089	

## Tilbehør

1007213	LED DRIVER , 10W, 700-mA, PHASE, incl. strain relief
1002423	LED driver MEDO 300 , dimmable DALI/1-10V

Indbygningsbredde	4.9 cm
Indbygningsdybde	7 cm
BIG WHITE side	217