




MILANDOS 4

white recessed ceiling light, 2700K 45°



The MILANDOS recessed ceiling light convinces with its compact design and innovative lighting properties. It shines above all with a true-to-life colour reproduction index of over 90 out of 60,000. With a UGR of 23, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends stylishly into any room. The spotlight is also quick and easy to install. Experience light with SLV – your reliable partner for all kinds of indoor lights for 40 years.



Tekniske data

Item no.	1005409
IP klasse	IP20
IK Vandalklasse	IK02
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	700mA
IP Tæthedegrad	III
Watt	8 W
Omgivelsestemperatur	30 °C
Lumen	640 lm
Farvetemperatur	2700 Kelvin
Spredningsvinkel	45 °
Farve	matt white/white
CRI	90
UGR ≤	23
LXXBXX-data	L80B50
Længde	13.6 cm
Bredde	5.6 cm
Højde	4.3 cm
Nettovægt	0.233 kg
Bruttovægt	0.293 kg
Indbygnings længde	13 cm

Lyskilde

1078067	
1078460	

Indbygningsbredde	4.9 cm
Indbygningsdybde	7 cm

Tilbehør

1007213	LED DRIVER , 10W, 700-mA, PHASE, incl. strain relief
1002423	LED driver MEDO 300 , dimmable DALI/1-10V