

MILANDOS 8



black recessed ceiling light, 2700K 45°

The MILANDOS recessed ceiling light convinces with its compact design and innovative lighting properties. It shines above all with a true-to-life colour reproduction index of over 90 out of 60,000. With its simple design, the square recessed ceiling light made of aluminium and polycarbonate (PC) blends stylishly into any room. With a UGR of 16, it conjures up a high-quality, glare-free light. The spotlight is also quick and easy to install. When will you test out the benefits of SLV's impressive indoor lights?

TECHNICAL DATA

Item no.	1005423
IP Code	IP 20
Impact resistance class	IK 02
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	16 W
Ambient temperature	30 °C
Lumen	1030 lm
Colour temperature	2700 Kelvin
Beam angle	45 °
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L80B50
Service life	60000 h
Risk Group	1
Length	25.6 cm
Width	5.6 cm
Height	4.3 cm
Net weight	0.4 kg

Light Source

1078067	
1078460	

Accessories

1002423	LED driver MEDO 300 , dimmable DALI/1-10V
1006202	LED Driver , 20W 700mA

Gross weight	0.428 kg
Shape of cut-out	square
Installation length	25 cm
Installation width	4.9 cm
Installation depth	7 cm
BIG WHITE Page	217