


MILANDOS 8

black recessed ceiling light, 3000K 45°



Minimalist, innovative and compact in design, the MILANDOS recessed ceiling light creates high-quality lighting. The true-to-life colour reproduction index of over 90 and the long LED lifespan of 60,000 hours also speak for the light. With a UGR of 16, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends seamlessly into any room. The spotlight is also quick and easy to install. When will you test out the benefits of SLV's impressive indoor lights?



Tekniske data

Item no.	1005424
IP klasse	IP20
IK Vandalklasse	IK02
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	700mA
IP Tæthedegrad	III
Watt	16 W
Omgivelsestemperatur	30 °C
Lumen	1040 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	45 °
Farve	matt black/black
CRI	90
UGR ≤	16
LXXBXX-data	L80B50
Længde	25.6 cm
Bredde	5.6 cm
Højde	4.3 cm
Nettovægt	0.388 kg
Bruttovægt	0.476 kg
Indbygnings længde	25 cm

Lyskilde

1078215	
998089	

Tilbehør

1002423	LED driver MEDO 300 , dimmable DALI/1-10V
1006202	LED Driver , 20W 700mA

Indbygningsbredde	4.9 cm
Indbygningsdybde	7 cm
BIG WHITE side	217