




NUMINOS® XS

black recessed ceiling light, 2700K 55°

The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



Tekniske data

Item no.	1005505
IP klasse	IP20/IP44
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	200mA
IP Tæthedsgard	III
Watt	7 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	640 lm
Farvetemperatur	2700 Kelvin
Spredningsvinkel	55 °
Farve	matt black
CRI	90
UGR ≤	25
LXXBXX-data	L80B50
Højde	4.5 cm
Diameter	6.5 cm
Nettovægt	0.114 kg
Bruttovægt	0.135 kg

Lyskilde

798300	
Tilbehør	
1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005614	NUMINOS® XS , frosted diffuser
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1005612	NUMINOS® XS , diffuser
1005610	LED Driver , 200mA 10-W, Quick Connector
1005615	NUMINOS® XS , black diffuser
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1005613	NUMINOS® XS , transparent diffuser
1006457	LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI

Indbygningsdybde	11 cm
Installations diameter	5.5 cm
BIG WHITE side	84