



NUMINOS® XS

white recessed ceiling light, 3000K 20°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?

TECHNICAL DATA

Item no.	1005527
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	730 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L80B50
Service life	50000 h
Risk Group	2
Height	4.5 cm
Diameter	6.5 cm

Light Source

798303	
--------	---

Accessories

1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005614	NUMINOS® XS , frosted diffuser
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1005612	NUMINOS® XS , diffuser
1005610	LED Driver , 200mA 10-W, Quick Connector
1005615	NUMINOS® XS , black diffuser
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1005613	NUMINOS® XS , transparent diffuser
1006457	LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI

Net weight	0.115 kg
Gross weight	0.135 kg
Shape of cut-out	round
Installation depth	11 cm
Installation diameter	5.5 cm
BIG WHITE Page	84