



NUMINOS® XS

white / black recessed ceiling light, 3000K 40°

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. The diverse downlights and spotlights make a thousand lighting design options possible. Like with the NUMINOS® XS recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

Item no.	1005529
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	670 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Risk Group	2
Height	4.5 cm
Diameter	6.5 cm

Light Source

798303	
--------	---

Accessories

1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005614	NUMINOS® XS , frosted diffuser
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1005612	NUMINOS® XS , diffuser
1005610	LED Driver , 200mA 10-W, Quick Connector
1005615	NUMINOS® XS , black diffuser
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1005613	NUMINOS® XS , transparent diffuser
1006457	LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI

Net weight	0.115 kg
Gross weight	0.135 kg
Shape of cut-out	round
Installation depth	11 cm
Installation diameter	5.5 cm
BIG WHITE Page	84