



## **NUMINOS® MOVE XS**

white / black recessed ceiling light, 2700K  $55^{\circ}$ 

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® MOVE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

## **TECHNICAL DATA**

Item no.	1005568
Rotating or tilting	rotary bar and tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	640 lm
Colour temperature	2700 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR≤	25
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Height	5.5 cm
	·



## **Light Source**

798300	A F
Accessories	
1006136	Numinos® XS Reducing ring , round 160/70mm white
1006135	Numinos® XS Reducing ring , round 160/70mm black
1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005614	NUMINOS® XS , frosted diffuser
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1005612	NUMINOS® XS , diffuser
1005610	LED Driver , 200mA 10- W, Quick Connector
1005615	NUMINOS® XS , black diffuser
1006137	Numinos® XS Reducing ring , square 160/70mm black
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1006138	Numinos® XS Reducing ring , square 160/70mm white
1005613	NUMINOS® XS , transparent diffuser
1006457	LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI

Diameter	8 cm
Net weight	0.135 kg
Gross weight	0.165 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	6.8 cm
BIG WHITE Page	86