



## NUMINOS® MOVE XS

## white / chrome recessed ceiling light, 3000K $20^\circ$

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® MOVE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

## **TECHNICAL DATA**

| Item no.                    | 1005582                 |
|-----------------------------|-------------------------|
| Rotating or tilting         | rotary bar and tiltable |
| IP Code                     | IP 20                   |
| Impact resistance class     | IK 02                   |
| Impact resistance           | 0.2 Joule               |
| Assembly                    | Recessed                |
| Assembly details            | Ceiling                 |
| Secondary power / voltage   | 200 mA                  |
| Safety class                | 111                     |
| Wattage                     | 7 W                     |
| Minimum ambient temperature | -20 °C                  |
| Maximum ambient temperature | 40 °C                   |
| Lumen                       | 730 lm                  |
| Colour temperature          | 3000 Kelvin             |
| Beam angle                  | 20 °                    |
| Color                       | white                   |
| CRI                         | 90                      |
| UGR≤                        | 16                      |
| LXXBXX data                 | L80B50                  |
| Service life                | 50000 h                 |
| Risk Group                  | 2                       |
| Height                      | 5.5 cm                  |
|                             |                         |



## Light Source

| 798303      | ₫ <b>F</b>  |
|-------------|---|
| Accessories |   |
| 1006136     | Numinos® XS Reducing<br>ring , round 160/70mm<br>white  |
| 1006135     | Numinos® XS Reducing<br>ring , round 160/70mm<br>black  |
| 1005609     | LED Driver , 200mA 10W<br>PHASE, Quick Connector  |
| 1005614     | NUMINOS® XS , frosted diffuser  |
| 1006454     | RF module Casambi for<br>LED bridge driver , single<br>colour                                       |
| 1006199     | RF module Zigbee for<br>DALI LED bridge driver ,<br>single colour                                   |
| 1005612     | NUMINOS® XS , diffuser  |
| 1005610     | LED Driver , 200mA 10-<br>W, Quick Connector  |
| 1005615     | NUMINOS® XS , black diffuser  |
| 1006137     | Numinos® XS Reducing<br>ring , square 160/70mm<br>black   |
| 1005611     | LED Driver , 200mA<br>13,5W DALI dimmable,<br>Quick Connector                                       |
| 1006138     | Numinos® XS Reducing<br>ring , square 160/70mm<br>white   |
| 1005613     | NUMINOS® XS , trans-<br>parent diffuser   |
| 1006457     | LED bridge driver , 12W,<br>200mA for NUMINOS®,<br>including radio interface<br>for RF module, DALI |

| Diameter              | 8 cm     |
|-----------------------|----------|
| Net weight            | 0.135 kg |
| Gross weight          | 0.165 kg |
| Shape of cut-out      | round    |
| Installation depth    | 8 cm     |
| Installation diameter | 6.8 cm   |
| BIG WHITE Page        | 86       |