




NUMINOS® MOVE XS

black / chrome recessed ceiling light, 4000K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® MOVE XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



Tekniske data

Item no.	1005597
IP klasse	IP20
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	200mA
IP Tæthedsgard	III
Watt	7 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	740 lm
Farvetemperatur	4000 Kelvin
Spredningsvinkel	55 °
Farve	matt black/glossy chrome
CRI	90
UGR ≤	25
LXXBXX-data	L80B50
Højde	5.5 cm
Diameter	8 cm
Nettovægt	0.148 kg
Bruttovægt	0.178 kg

Lyskilde

798305	
--------	---

Tilbehør

1006136	Numinos® XS Reducing ring , round 160/70mm white
1006135	Numinos® XS Reducing ring , round 160/70mm black
1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005614	NUMINOS® XS , frosted diffuser
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1005612	NUMINOS® XS , diffuser
1005610	LED Driver , 200mA 10-W, Quick Connector
1005615	NUMINOS® XS , black diffuser
1006137	Numinos® XS Reducing ring , square 160/70mm black
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1006138	Numinos® XS Reducing ring , square 160/70mm white
1005613	NUMINOS® XS , transparent diffuser
1006457	LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI

Indbygningsdybde	8 cm
Installations diameter	6.8 cm
BIG WHITE side	86