



## NUMINOS® MOVE XS

white recessed ceiling light, 4000K 20°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® MOVE XS recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

|                             |                         |
|-----------------------------|-------------------------|
| Item no.                    | 1005599                 |
| Rotating or tilting         | rotary bar and tiltable |
| IP Code                     | IP 20                   |
| Impact resistance class     | IK 02                   |
| Impact resistance           | 0.2 Joule               |
| Assembly                    | Recessed                |
| Assembly details            | Ceiling                 |
| Secondary power / voltage   | 200 mA                  |
| Safety class                | III                     |
| Wattage                     | 7 W                     |
| Minimum ambient temperature | -20 °C                  |
| Maximum ambient temperature | 40 °C                   |
| Lumen                       | 750 lm                  |
| Colour temperature          | 4000 Kelvin             |
| Beam angle                  | 20 °                    |
| Color                       | white                   |
| CRI                         | 90                      |
| UGR ≤                       | 16                      |
| LXXBXX data                 | L80B50                  |
| Service life                | 50000 h                 |
| Risk Group                  | 2                       |
| Height                      | 5.5 cm                  |

## Light Source

|        |   |
|--------|---|
| 798305 |  |
|--------|---|

## Accessories

|         |  |
|---------|--|
| 1006136 | Numinos® XS Reducing ring , round 160/70mm white   |
| 1006135 | Numinos® XS Reducing ring , round 160/70mm black   |
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector  |
| 1005614 | NUMINOS® XS , frosted diffuser   |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1005612 | NUMINOS® XS , diffuser   |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector   |
| 1005615 | NUMINOS® XS , black diffuser   |
| 1006137 | Numinos® XS Reducing ring , square 160/70mm black  |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector                                    |
| 1006138 | Numinos® XS Reducing ring , square 160/70mm white  |
| 1005613 | NUMINOS® XS , transparent diffuser   |
| 1006457 | LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI |

|                       |          |
|-----------------------|----------|
| Diameter              | 8 cm     |
| Net weight            | 0.135 kg |
| Gross weight          | 0.165 kg |
| Shape of cut-out      | round    |
| Installation depth    | 8 cm     |
| Installation diameter | 6.8 cm   |
| BIG WHITE Page        | 86       |