



NUMINOS® MOVE XS

white/black recessed ceiling light, 4000K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMI-NOS® MOVE XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

Item no.	1005606
Rotating or tilting	rotary bar and tiltable
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	710 lm
Colour temperature	4000 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR≤	25
LXXBXX data	L80B50
Service life	50000 h
Risk Group	2
Height	5.5 cm



Light Source

A E
Numinos® XS Reducing ring , round 160/70mm white
Numinos® XS Reducing ring , round 160/70mm black
LED Driver , 200mA 10W PHASE, Quick Connector
NUMINOS® XS , frosted diffuser
RF module Casambi for LED bridge driver , single colour
RF module Zigbee for DALI LED bridge driver , single colour
NUMINOS® XS , diffuser
LED Driver , 200mA 10- W, Quick Connector
NUMINOS® XS , black diffuser
Numinos® XS Reducing ring , square 160/70mm black
LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
Numinos® XS Reducing ring , square 160/70mm white
NUMINOS® XS , trans- parent diffuser
LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI

Diameter	8 cm
Net weight	0.135 kg
Gross weight	0.165 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	6.8 cm
BIG WHITE Page	86