



NUMINOS® XL PHASE

white / black ceiling mounted light, 36W 4000K 24 $^{\circ}$

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® XL PHASE indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3800 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.

TECHNICAL DATA

| Item no. | 1005702 |
|-----------------------------------|-------------------|
| Number of different light outlets | 1 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 900 mA |
| Safety class | I |
| Wattage | 36 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Level of inrush current | 4.64 A |
| Duration of inrush current | 224 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 3800 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 24 ° |
| Color | white |
| CRI | 90 |
| UGR≤ | 19 |
| LXXBXX data | L80B50 |
| | |



Light Source

| 791850 | A E |
|-------------|--------------------------------|
| Accessories | |
| 1006170 | NUMINOS® XL , white front ring |

| Service life | 50000 h |
|----------------|---------|
| Risk Group | 1 |
| Height | 25.8 cm |
| Diameter | 12 cm |
| Net weight | 1.63 kg |
| Gross weight | 2 kg |
| BIG WHITE Page | 105 |