




## NUMINOS® XL PHASE

black pendant light, 36W 4000K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® XL PHASE, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 36 watts, luminous flux of 3760 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.	1005718
Number of different light outlets	1
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	4.64 A
Duration of inrush current	224 µs
Stroboscopic effect (SVM)	0.02
Lumen	3760 lm
Colour temperature	4000 Kelvin
Beam angle	36 °
Color	black
CRI	90
UGR ≤	19
LXXBXX data	L80B50

## Light Source

791850	
--------	---

<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Height</b>	25.8 cm
<b>Diameter</b>	12 cm
<b>Pendant length</b>	250 cm
<b>Net weight</b>	2 kg
<b>Gross weight</b>	2.25 kg
<b>BIG WHITE Page</b>	105