




## NUMINOS® XL | 3-phase, PHASE

**NUMINOS® XL 3Ph., PHASE, 3~ Spotlight, cylindrical, 3000 K, 28 Watt, trailing edge, 24°, matt white / matt black**

The NUMINOS® XL 3Ph. spot is a cylindrical 3-phase spotlight designed for mounting on ceiling track systems. It is suitable for indoor use, for example in commercial or public areas where targeted lighting is required. With a luminous flux of 3550 lumens at 28 watts and a colour temperature of 3000 K, the spot produces warm white light with a beam angle of 24 degrees. The housing is made of aluminium and is available in matt white or matt black. Dimming is carried out via phase-cut control (trailing edge). The IP20 protection rating protects the device against contact and solid foreign objects. With a product length of 25.8 cm, a diameter of 12 cm, and a height of 18.5 cm, the spot offers compact dimensions for flexible application options.



### Light source

2093861



|                                   |                    |
|-----------------------------------|--------------------|
| Item no.                          | 1005732            |
| Lamps included                    | No                 |
| Number of different light outlets | 1                  |
| IP Code                           | IP20               |
| Assembly                          | Track              |
| Assembly details                  | Ceiling,           |
| Dimmable                          | true               |
| Dimming technology                | trailing edge      |
| Primary nominal voltage           | 220-240V ~ 50/60Hz |
| Secondary power / voltage         | 700 mA             |
| Safety class                      | I                  |
| Wattage                           | 28 W               |
| Minimum ambient temperature       | -20°C              |
| Maximum ambient temperature       | 45°C               |
| Number of luminaires at LS B16A   | 54.0               |
| Number of luminaires at LS C16A   | 54.0               |
| Level of inrush current           | 10 A               |
| Duration of inrush current        | 50 µs              |
| Beam angle                        | 24°                |
| Color                             | white              |
| CRI                               | 90                 |
| UGR ≤                             | 16                 |
| LXXBXX data                       | L90B10             |
| Service life                      | 50 000 h           |
| Risk Group                        | 1                  |
| Length                            | 25.8 cm            |
| Height                            | 18.5 cm            |
| Diameter                          | 12 cm              |
| Net weight                        | 1.64 kg            |

## Accessories

|         |                                      |
|---------|--------------------------------------|
| 1006170 | NUMINOS® XL, white front ring        |
| 1008147 | NUMINOS® XL, front ring, matt gold   |
| 1008143 | NUMINOS® XL, front ring, matt copper |