



NUMINOS® XL PHASE

white / black 3-phase spot, 36W 4000K 36°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® XL PHASE 3-phase system light LED, which convinces with best workmanship and light quality. The spotlight is perfect for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3760 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1005739 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| Assembly details | Track Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 900 mA |
| Safety class | I |
| Wattage | 36 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Level of inrush current | 4.64 A |
| Duration of inrush current | 224 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 3760 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 36 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 19 |
| LXXBXX data | L80B50 |

Light Source

| | |
|--------|---|
| 791850 |  |
|--------|---|

| | |
|-----------------------|---------|
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 25.8 cm |
| Height | 20 cm |
| Diameter | 12 cm |
| Net weight | 1.63 kg |
| Gross weight | 2 kg |
| BIG WHITE Page | 113 |