




## NUMINOS® SPOT DALI XL

black ceiling mounted light, 36W 3000K 24°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® SPOT DALI XL indoor ceiling-mounted light LED, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3530 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



### TECHNICAL DATA

Item no.	1005747
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	18
Number of luminaires at LS C16A	18
Level of inrush current	15 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0
Lumen	3530 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	black

## Light Source

791823	
--------	---

## Accessories

1006170	NUMINOS® XL , white front ring
---------	--------------------------------

CRI	90
UGR ≤	19
LXXBXX data	L80B50
Service life	50000 h
Length	25.8 cm
Height	20 cm
Diameter	12 cm
Net weight	1.5 kg
Gross weight	2 kg
BIG WHITE Page	101