



NUMINOS® DALI XL

black ceiling mounted light, 36W 3000K 24°

The NUMINOS light system from SLV skilfully combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® DALI XL indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The recessed ceiling light convinces with a power consumption of 36 watts, luminous flux of 3530 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?

TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1005765 |
| Number of different light outlets | 1 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 900 mA |
| Safety class | I |
| Wattage | 36 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Number of luminaires at LS B16A | 18 |
| Number of luminaires at LS C16A | 18 |
| Level of inrush current | 15 A |
| Duration of inrush current | 100 µs |
| Stroboscopic effect (SVM) | 0 |
| Lumen | 3530 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 24 ° |
| Color | black |
| CRI | 90 |

Light Source

| | |
|--------|---|
| 791823 |  |
|--------|---|

Accessories

| | |
|---------|--------------------------------|
| 1006170 | NUMINOS® XL , white front ring |
|---------|--------------------------------|

| | |
|----------------|---------|
| UGR ≤ | 19 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Height | 25.8 cm |
| Diameter | 12 cm |
| Net weight | 1.5 kg |
| Gross weight | 1.85 kg |
| BIG WHITE Page | 105 |