NUMINOS® XL | 3Ph., DALI

NUMINOS® XL 3Ph., DALI, 3~ Spotlight, cylindrical, 3000 K, 27 Watt, DALI, 36°, matt black

The NUMINOS® XL 3-phase DALI spotlight features a cylindrical luminaire body designed for mounting on ceiling track systems. With a luminous flux of 3550 lumens at 27 watts and a colour temperature of 3000 K, this luminaire is suitable for targeted lighting tasks in indoor environments. The 36° beam angle allows for precise light control. The housing is made of aluminium and finished in matte black. The luminaire includes DALI-2 and touch dimming functions, enabling flexible light control. With an IP20 rating, it is suitable for use in dust-protected indoor areas. Measuring 20.8 cm in length and 12 cm in diameter, the spotlight offers a compact design with a discreet, functional appearance.



Light source

2093861	A G D

Item no.	1005802
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Track
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	58.0
Number of luminaires at LS C16A	58.0
Level of inrush current	2.83 A
Duration of inrush current	188 µs
Beam angle	36°
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	20.8 cm
Height	20 cm
Diameter	12 cm
Net weight	1.55 kg

Accessories

1006170	NUMINOS® XL, white front ring
1008147	NUMINOS® XL, front ring, matt gold
1008143	NUMINOS® XL, front ring, matt copper