




NUMINOS® XL | 3Ph., DALI

NUMINOS® XL 3Ph., DALI, 3~ Spotlight, cylindrical, 3000 K, 27 Watt, DALI, 24°, matt white / matt black

The NUMINOS® XL 3Ph. DALI 3~ Spot is a cylindrically shaped spotlight designed for ceiling track system mounting. It is suitable for use in professional indoor environments where precise and directed lighting is required. With a luminous flux of 3550 lumens at a colour temperature of 3000 K, it produces warm white light with a beam angle of 24 degrees. The housing is made of aluminium and is available in matt white or matt black. The luminaire features DALI 2 and touch dimming functions for flexible light control. The IP20 protection rating makes the spot suitable for use in dust-protected indoor areas. With a product length of 20.8 cm and a diameter of 12 cm, the spot offers a compact design for versatile lighting applications.



Light source

2093861



Item no.	1005804
Lamps included	No
Number of different light outlets	1
IP Code	IP20
Assembly	Track
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2Touch
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	28 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	58.0
Number of luminaires at LS C16A	58.0
Level of inrush current	2.83 A
Duration of inrush current	188 µs
Beam angle	24°
Color	white
CRI	90
UGR ≤	16
LXXBXX data	L90B10
Service life	50 000 h
Risk Group	1
Length	20.8 cm
Height	20 cm
Diameter	12 cm
Net weight	1.55 kg

Accessories

1006170	NUMINOS® XL, white front ring
1008147	NUMINOS® XL, front ring, matt gold
1008143	NUMINOS® XL, front ring, matt copper