




NUMINOS® GIMBLE XS

white recessed ceiling light, 3000K 20°

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. The different downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® GIMBLE XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



Tekniske data

Item no.	1005841
Antal lysåbninger	1
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	200mA
IP Tæthedsggrad	III
Watt	7 W
Lumen	730 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	20 °
Farve	matt white/white
CRI	90
UGR ≤	16
LXXBXX-data	L80B50
Højde	5.7 cm
Diameter	8 cm
Nettovægt	0.14 kg
Bruttovægt	0.17 kg
Indbygningsdybde	8 cm
Installations diameter	6.8 cm
BIG WHITE side	88

Lyskilde

798303	
--------	---

Tilbehør

1006136	Numinos® XS Reducing ring , round 160/70mm white
1006135	Numinos® XS Reducing ring , round 160/70mm black
1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005614	NUMINOS® XS , frosted diffuser
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1005612	NUMINOS® XS , diffuser
1005610	LED Driver , 200mA 10-W, Quick Connector
1005615	NUMINOS® XS , black diffuser
1006137	Numinos® XS Reducing ring , square 160/70mm black
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1006138	Numinos® XS Reducing ring , square 160/70mm white
1005613	NUMINOS® XS , transparent diffuser
1006457	LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI