



## NUMINOS® GIMBLE XS

white / black recessed ceiling light, 3000K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?

### TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1005846                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 200 mA                  |
| Safety class                      | III                     |
| Wattage                           | 7 W                     |
| Lumen                             | 690 lm                  |
| Colour temperature                | 3000 Kelvin             |
| Beam angle                        | 55 °                    |
| Color                             | white                   |
| CRI                               | 90                      |
| UGR ≤                             | 25                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 5.7 cm                  |
| Diameter                          | 8 cm                    |
| Net weight                        | 0.13 kg                 |
| Gross weight                      | 0.15 kg                 |
| Shape of cut-out                  | round                   |

## Light Source

|        |   |
|--------|---|
| 798303 |  |
|--------|---|

## Accessories

|         |  |
|---------|--|
| 1006136 | Numinos® XS Reducing ring , round 160/70mm white   |
| 1006135 | Numinos® XS Reducing ring , round 160/70mm black   |
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector  |
| 1005614 | NUMINOS® XS , frosted diffuser   |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1005612 | NUMINOS® XS , diffuser   |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector   |
| 1005615 | NUMINOS® XS , black diffuser   |
| 1006137 | Numinos® XS Reducing ring , square 160/70mm black  |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector                                    |
| 1006138 | Numinos® XS Reducing ring , square 160/70mm white  |
| 1005613 | NUMINOS® XS , transparent diffuser   |
| 1006457 | LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI |

|                       |        |
|-----------------------|--------|
| Installation depth    | 8 cm   |
| Installation diameter | 6.8 cm |
| BIG WHITE Page        | 88     |