




NUMINOS® GIMBLE S

black / chrome recessed ceiling light, 4000K 40°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® GIMBLE S recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When will you choose SLV's modular variety?



Tekniske data

Item no.	1005908
Antal lysåbninger	1
IP klasse	IP20
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	250mA
IP Tæthedsggrad	III
Watt	8.6 W
Lumen	750 lm
Farvetemperatur	4000 Kelvin
Spredningsvinkel	40 °
Farve	matt black/chrome
CRI	90
UGR ≤	19
LXXBXX-data	L80B50
Højde	7 cm
Diameter	10 cm
Nettovægt	0.213 kg
Bruttovægt	0.25 kg
Indbygningsdybde	7 cm
Installations diameter	9 cm
BIG WHITE side	88

Lyskilde

791831	
--------	---

Tilbehør

1006458	LED bridge driver , 12W, 250mA for NUMINOS®, including radio interface for RF module, DALI
1004789	NUMINOS® S , diffuser Wabe
1004067	LED driver , 15W 250mA DALI
1004788	NUMINOS® S , diffuser Frosted
1004787	NUMINOS® S , diffuser Prisma
1004786	NUMINOS® S , diffuser Ellipse
1006139	Numinos® S Reducing ring , round 160/100mm black
1006454	RF module Casambi for LED bridge driver , single colour
1004058	LED driver , 6.5-10W 250mA
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006140	Numinos® S Reducing ring , round 160/100mm white
1006142	Numinos® S Reducing ring , square 160/100mm white
1004055	LED driver , 6.5-10W 250mA PHASE
1006141	Numinos® S Reducing ring , square 160/100mm black