



NUMINOS® GIMBLE XL

black / chrome recessed ceiling light, 2700K 240°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE XL, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

TECHNICAL DATA

Item no.	1006031
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	1000/1050 mA
Safety class	III
Wattage	37.4 W
Lumen	3400 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Height	13.5 cm
Diameter	19 cm
Net weight	0.85 kg
Gross weight	1 kg
Shape of cut-out	round

Light Source

791857	
--------	---

Accessories

1006152	Numinos® XL Reducing ring , round 240/180mm white
1006151	Numinos® XL Reducing ring , round 240/180mm black
1004800	NUMINOS® XL , diffuser Frosted
1004071	LED driver 4.2-50W 1050mA DALI
1006454	RF module Casambi for LED bridge driver , single colour
1006154	Numinos® XL Reducing ring , square 240/180mm white
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1004798	NUMINOS® XL , diffuser Ellipse
1006153	Numinos® XL Reducing ring , square 240/180mm black
1004059	LED driverm 40W multi mA
1006461	LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI
1004066	LED driver , 28-40W 1000mA PHASE
1004801	NUMINOS® XL , diffuser Wabe
1004799	NUMINOS® XL , diffuser Prisma

Installation depth	13.5 cm
Installation diameter	17.5 cm
BIG WHITE Page	89