




NUMINOS® GIMBLE XL

white / chrome recessed ceiling light, 3000K 40°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® GIMBLE XL recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When do you choose NUMINOS® from SLV?



Tekniske data

Item no.	1006061
Antal lysåbninger	1
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	1000/1050mA
IP Tæthedsggrad	III
Watt	37.4 W
Lumen	3500 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	40 °
Farve	matt white/chrome
CRI	90
UGR ≤	22
LXXBXX-data	L80B50
Højde	13.5 cm
Diameter	19 cm
Nettovægt	0.86 kg
Bruttovægt	1.071 kg
Indbygningsdybde	13.5 cm
Installations diameter	17.5 cm
BIG WHITE side	89

Lyskilde

791823	
--------	---

Tilbehør

1006152	Numinos® XL Reducing ring , round 240/180mm white
1006151	Numinos® XL Reducing ring , round 240/180mm black
1004800	NUMINOS® XL , diffuser Frosted
1004071	LED driver 4.2-50W 1050mA DALI
1006454	RF module Casambi for LED bridge driver , single colour
1006154	Numinos® XL Reducing ring , square 240/180mm white
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1004798	NUMINOS® XL , diffuser Ellipse
1006153	Numinos® XL Reducing ring , square 240/180mm black
1004059	LED driverm 40W multi mA
1006461	LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI
1004066	LED driver , 28-40W 1000mA PHASE
1004801	NUMINOS® XL , diffuser Wabe
1004799	NUMINOS® XL , diffuser Prisma