



## NUMINOS® ZOOM M PHASE

white 3-phase spot, 20W 3000K 15-60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Like with the NUMINOS® ZOOM M PHASE 3-phase system light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. Installation is then done in no time at all. When will you choose SLV's modular variety?

### TECHNICAL DATA

Item no.	1006111
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Stroboscopic effect (SVM)	0.03
Lumen	750-1800 lm
Colour temperature	3000 Kelvin
Beam angle	15 °
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L70B50
Service life	40000 h
Risk Group	1

## Light Source

791822	
--------	---

<b>Length</b>	19 cm
<b>Height</b>	16.5 cm
<b>Diameter</b>	8.5 cm
<b>Net weight</b>	0.989 kg
<b>Gross weight</b>	1.311 kg
<b>BIG WHITE Page</b>	115