




M-POL S Polehead

Lamp head, anthracite, 19W, 890/950lm, 2700/3000K, CRI90, DALI

Suitable for universal use, featuring a sophisticated design and high output: the lamp heads and diffusers in the first DALI-dimmable SLV outdoor family are ideal for a variety of applications. With a CRI of over 90, 890 / 950 lumen, and an LED lifespan of 50,000 hours, the cylindrical M-POL S Polehead can satisfy even the most challenging requirements. Choose a specific lamp head as preferred for your lighting projects.



TECHNICAL DATA

Item no.	1006389
IP Code	IP 65
Impact resistance class	IK 10
Assembly details	Ground with Acc.
Dimmable	Yes
Dimming technology	DALI
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Wattage	19 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Operating efficiency (LOR)	0,434
Rated standby power	0.5 W
Number of luminaires at LS B16A	8
Number of luminaires at LS C16A	16
Level of inrush current	10 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	890/950 lm
Colour temperature	2700/3000 Kelvin
Color	anthracite
CRI	90

Light Source

1370514	
---------	---

Accessories

1006381	M-POL 90 Pole , Bollard, anthracite, 83.4cm
1006453	Connection box , 5-pin, IP68, black, DALI
1006379	M-POL 30 Pole , Bollard, anthracite, 23.4cm
1006380	M-POL 60 Pole , Bollard, anthracite, 53.4cm
1006382	M-POL ground anchor , stainless steel
228725	CONNECTION BOX , 5-pin, IP68

LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Height	16.4 cm
Diameter	12.09 cm
Net weight	1.148 kg
Gross weight	1.228 kg
BIG WHITE Page	617