




MEDO® PRO 40

wall- and ceiling-mounted light, round, 3000/4000K, 19W, DALI, Touch, 70°, UGR<19, DC, black

With MEDO® PRO DC, you benefit from all the technical advantages of the prismatic MEDO® PRO version with UGR<19. It is DALI controllable and impresses with its service life of L80B10@50,000h, eligible energy efficiency from 120 lm/W and a higher indirect light component. Efficiency is also the order of the day when it comes to installation, which is particularly fast thanks to our EasyBase. The improved protection code IP50 and an outstanding CRI>90 colour reproduction index ensure exceptional quality. Two elegant casing colours and a CCT switch that enables you to choose between 3000 K and 4000 K lets you personalise your lighting situation. In addition, you can be sure that the MEDO® PRO DC lights will continue to shine groundbreakingly even if the power supply fails, thanks to the integrated DC driver.



Tekniske data

Item no.	1006414
IP klasse	IP50
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Montering	Surface
Monterings detaljer	Ceiling, Ceiling with Acc., Wall
Dæmpbar	Ja
Dæmpningstype	DALI, Touch
Antal lamper ved videresløjning	20
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	500mA
IP Tæthedsggrad	I
Watt	19 W
Omgivelsestemperatur	25 °C
Min omgivelsestemperatur	-25 °C
Max omgivelsestemperatur	45 °C
Lumen	2400/2500 lm
Farvetemperatur	3000/4000 Kelvin
Spredningsvinkel	80 °
Farve	matt black
CRI	90
UGR ≤	19

Lyskilde

1807453	
Tilbehør	
1001952	MEDO 5m suspension , black
1001950	MEDO 5m suspension , white
135250	SUSPENSION SET , for MEDO round pendant, round, black, 5-wire
1001951	MEDO 5m suspension , silver-grey
135251	SUSPENSION SET , for MEDO round pendant, round, white, 5-wire
135254	SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire

LXXBXX-data	L80B10
Højde	9.2 cm
Diameter	38 cm
Nettovægt	1.998 kg
Bruttovægt	3.019 kg
BIG WHITE side	157