




IN-LINE 22 48V TRACK

opal, DALI, spot, white 7.3W, 540lm, 2700K, CRI90, 95°

Plain linear luminaires for a particularly elegant look: the IN-LINE spotlight is concealed within a 48V TRACK system, allowing only the best feature to surface: high-quality light with a 95° beam angle in various lumen and natural colour reproduction (CRI>90). The DALI-compatible IN-LINE linear luminaires are also quick and easy to install via a track adapter.



Tekniske data

Item no.	1006616
Antal lysåbninger	1
IP klasse	IP20
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Monterings detaljer	Track,Track Ceiling,Track Wall
Dæmpbar	Ja
Dæmpningstype	DALI 2
Primær spænding	48V
Sekundær strøm / spænding	350mA
IP Tæthedsgrad	III
Watt	7.3 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	35 °C
Lumen	540 lm
Farvetemperatur	2700 Kelvin
Spredningsvinkel	95 °
Farve	matt white
CRI	90
UGR ≤	28
LXXBXX-data	L80B50
Længde	22 cm

Lyskilde

	
--	---

Bredde	2.2 cm
Højde	5.5 cm
Nettovægt	0.181 kg
Bruttovægt	0.216 kg
BIG WHITE side	473