




IN-LINE 44 48V TRACK

opal, DALI, spot, black 14W, 1140lm, 2700K, CRI90, 95°

Plain linear luminaires for a particularly elegant look: the IN-LINE spotlight is concealed within a 48V TRACK system, allowing only the best feature to surface: high-quality light with a 35° beam angle in various lumen and natural colour reproduction (CRI>90). The DALI-compatible IN-LINE linear luminaires are also quick and easy to install via a track adapter.



TECHNICAL DATA

| | |
|-----------------------------------|--------------------------------|
| Item no. | 1006621 |
| Number of different light outlets | 1 |
| IP Code | IP 20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly details | Track,Track Ceiling,Track Wall |
| Dimmable | Yes |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 48V |
| Secondary power / voltage | 350 mA |
| Safety class | III |
| Wattage | 14 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Network rated standby power | 0.5 W |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 1140 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 95 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 28 |

Light Source



| | |
|-----------------------|----------|
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 43.5 cm |
| Width | 2.2 cm |
| Height | 2.5 cm |
| Net weight | 0.279 kg |
| Gross weight | 0.299 kg |
| BIG WHITE Page | 475 |