




IN-LINE 44 48V TRACK

opal, DALI, spot, white 14W, 1180lm, 3000K, CRI90, 95°

Plain linear luminaires for a particularly elegant look: the IN-LINE spotlight is concealed within a 48V TRACK system, allowing only the best feature to surface: high-quality light with a 95° beam angle in various lumen and natural colour reproduction (CRI>90). The DALI-compatible IN-LINE linear luminaires are also quick and easy to install via a track adapter.



Tekniske data

Item no.	1006624
Antal lysåbninger	1
IP klasse	IP20
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Monterings detaljer	Track,Track Ceiling,Track Wall
Dæmpbar	Ja
Dæmpningstype	DALI 2
Primær spænding	48V
Sekundær strøm / spænding	350mA
IP Tæthedsgard	III
Watt	14 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	35 °C
Lumen	1180 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	95 °
Farve	matt white
CRI	90
UGR ≤	28
LXXBXX-data	L80B50
Længde	43.5 cm

Lyskilde

	
--	---

Bredde	2.2 cm
Højde	2.5 cm
Nettovægt	0.29 kg
Bruttovægt	0.351 kg
BIG WHITE side	475