


# NUMINOS® XS | 48V, DALI

**NUMINOS® XS 48V TRACK, DALI, spot, white / black, 8.7 W, 670 lm, 3000 K, CRI 90, 40°**

High-quality minimalism across the board: the compact NUMINOS® spotlights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700 K/3000 K/4000 K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The adjustable and pivoting spotlights are quick and easy to install thanks to the track adapter.




## Light source

| | |
|---|---|
| 798303 | A G F |

| | |
|---|---|
| **Item no.** | 1006681 |
| **Lamps included** | No |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary bar and tiltable |
| **IP Code** | IP20 |
| **Impact resistance class** | IK02 |
| **Impact resistance** | 0.2 Joule |
| **Dimmable** | true |
| **Dimming technology** | DALI 2 |
| **Primary nominal voltage** | 48V DC |
| **Secondary power / voltage** | 200 mA |
| **Safety class** | III |
| **Wattage** | 9 W |
| **Minimum ambient temperature** | -20°C |
| **Maximum ambient temperature** | 35°C |
| **Beam angle** | 40° |
| **Color** | white/black |
| **CRI** | 90 |
| **UGR ≤** | 22 |
| **LXXBXX data** | L80B50 |
| **Service life** | 50 000 h |
| **Risk Group** | 2 |
| **Height** | 8 cm |
| **Diameter** | 5 cm |
| **Net weight** | 0.19 kg |
| **Gross weight** | 0.27 kg |
| **BIG WHITE Page** | 443 |

## Accessories

| | |
|---|---|
| **1005612** | NUMINOS® XS, diffuser |
| **1005613** | NUMINOS® XS, transparent diffuser |
| **1005614** | NUMINOS® XS, frosted diffuser |
| **1005615** | NUMINOS® XS, black diffuser |