


NUMINOS® S | 48V, DALI

NUMINOS® S, 48V spotlight, round, 4000 K, 16 W, DALI 2, 55°, matt white / glossy chrome

High-quality minimalism across the board: the compact NUMINOS® spotlights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700 K/3000 K/4000 K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The adjustable and pivoting spotlights are quick and easy to install thanks to the track adapter.



Light source

791831	A E

Item no.	1006758
Lamps included	No
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	48V DC
Secondary power / voltage	350 mA
Safety class	III
Wattage	16 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	35°C
Beam angle	55°
Color	white/chrome
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50 000 h
Risk Group	1
Height	9 cm
Diameter	6 cm
Net weight	0.36 kg
Gross weight	0.47 kg
BIG WHITE Page	445

Accessories

1004786	NUMINOS® S, diffuser Ellipse
1004787	NUMINOS® S, diffuser Prisma
1004788	NUMINOS® S, diffuser Frosted
1004789	NUMINOS® S, diffuser Wabe