# NUMINOS® S | 48V, DALI

**NUMINOS® S 48V TRACK, DALI, pendant light, black / black, 16 W, 1030 lm, 3000 K, CRI 90, 55°**

High-quality minimalism across the board: the compact NUMINOS® pendant lights provide elegant yet effective illumination with a 48V track system. They also perfectly complement the most discerning room designs with their clear, cylindrical shape. The brightness, light colour (2700 K/3000 K/4000 K) and half-peak divergence (20°/ 40°/55°) of these DALI-compatible spotlights can be adjusted as desired. The aluminium housing is available in black, white and chrome. A CRI value over 90 ensures natural colour reproduction. The pendant lights are quick and easy to install thanks to the track adapter.




## Light source

| | |
|---|---|
| 791815 | A↑G E |

| | |
|---|---|
| Item no. | 1006837 |
| Lamps included | No |
| Number of different light outlets | 1 |
| IP Code | IP20 |
| Impact resistance class | IK02 |
| Impact resistance | 0.2 Joule |
| Dimmable | true |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 48V DC |
| Secondary power / voltage | 350 mA |
| Safety class | III |
| Wattage | 16 W |
| Minimum ambient temperature | -20°C |
| Maximum ambient temperature | 35°C |
| Beam angle | 55° |
| Color | black/black |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| Service life | 50 000 h |
| Risk Group | 1 |
| Height | 12.5 cm |
| Diameter | 6 cm |
| Pendant length | 150.0000 cm |
| Net weight | 0.37 kg |
| Gross weight | 0.48 kg |
| BIG WHITE Page | 449 |

## Accessories

| | |
|---|---|
| **1004786** | NUMINOS® S, diffuser Ellipse |
| **1004787** | NUMINOS® S, diffuser Prisma |
| **1004788** | NUMINOS® S, diffuser Frosted |
| **1004789** | NUMINOS® S, diffuser Wabe |