




## NUMINOS® PROJECTOR XS

recessed ceiling light, 2700 K, 20°, cylindrical, black / black

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700K/3000K/4000K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



### TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1006867                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 200 mA                  |
| Safety class                      | III                     |
| Wattage                           | 7 W                     |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 640 lm                  |
| Colour temperature                | 2700 Kelvin             |
| Beam angle                        | 20 °                    |
| Color                             | black                   |
| CRI                               | 90                      |
| UGR ≤                             | 16                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Length                            | 8 cm                    |
| Diameter                          | 4.9 cm                  |
| Net weight                        | 0.24 kg                 |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 798300 |  |
|--------|-----------------------------------------------------------------------------------|

### Accessories

|         |                                                                                            |
|---------|--------------------------------------------------------------------------------------------|
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector                                              |
| 1005614 | NUMINOS® XS , frosted diffuser                                                             |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1005612 | NUMINOS® XS , diffuser                                                                     |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector                                                   |
| 1005615 | NUMINOS® XS , black diffuser                                                               |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector                                    |
| 1005613 | NUMINOS® XS , transparent diffuser                                                         |
| 1006457 | LED bridge driver , 12W, 200mA for NUMINOS®, including radio interface for RF module, DALI |

|                       |          |
|-----------------------|----------|
| Gross weight          | 0.257 kg |
| Shape of cut-out      | round    |
| Installation depth    | 10 cm    |
| Installation diameter | 6.8 cm   |
| BIG WHITE Page        | 92       |