




NUMINOS® PROJECTOR M

recessed ceiling light, 3000 K, 20°, cylindrical, black / chrome

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700K/3000K/4000K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



Tekniske data

Item no.	1006995
Antal lysåbninger	1
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	500mA
IP Tæthedsgard	III
Watt	17.5 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	1550 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	20 °
Farve	matt black/glossy chrome
CRI	90
UGR ≤	22
LXXBXX-data	L80B50
Længde	13 cm
Diameter	8 cm
Nettovægt	0.757 kg
Bruttovægt	0.911 kg
Indbygningsdybde	15 cm
Installations diameter	10.5 cm

Lyskilde

791822		BIG WHITE side	93
--------	---	----------------	----

Tilbehør

1004792	NUMINOS® M , diffuser Frosted
1004069	LED driver , 29W 500mA
1004064	LED driver , 21-29.5W 500/600/700mA
1006459	LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI
1004054	LED driver , 20W 500mA PHASE
1006454	RF module Casambi for LED bridge driver , single colour
1004793	NUMINOS® M , diffuser Wabe
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma