




NUMINOS® PROJECTOR L

recessed ceiling light, 2700 K, 40°, cylindrical, white / black

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700K/3000K/4000K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



Tekniske data

| | |
|---------------------------|-----------------------|
| Item no. | 1007041 |
| Antal lysåbninger | 1 |
| Montering | Recessed |
| Monterings detaljer | Ceiling |
| Sekundær strøm / spænding | 700mA |
| IP Tæthedsgrad | III |
| Watt | 25.4 W |
| Min omgivelsestemperatur | -20 °C |
| Max omgivelsestemperatur | 40 °C |
| Lumen | 2150 lm |
| Farvetemperatur | 2700 Kelvin |
| Spredningsvinkel | 40 ° |
| Farve | matt white/matt black |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX-data | L80B50 |
| Længde | 13 cm |
| Diameter | 10 cm |
| Nettovægt | 0.995 kg |
| Bruttovægt | 1.2 kg |
| Indbygningsdybde | 15 cm |
| Installations diameter | 13 cm |

Lyskilde

| | | | |
|--------|---|----------------|----|
| 791800 |  | BIG WHITE side | 93 |
|--------|---|----------------|----|

Tilbehør

| | |
|---------|---|
| 1004062 | LED driver , 21-29.5W 500/600/700mA for Numi- nos Downlight Serie |
| 1004795 | NUMINOS® L , diffuser Prisma |
| 1004796 | NUMINOS® L , diffuser Frosted |
| 1006460 | LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004794 | NUMINOS® L , diffuser Ellipse |
| 1006454 | RF module Casambi for LED bridge driver , single colour |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour |
| 1004070 | LED driver , 40W 700mA DALI |
| 1004797 | NUMINOS® L , diffuser Wabe |
| 1004065 | LED driver , 30W 700mA |