




UNIVERSAL DOWNLIGHT PHASE recessed light

IP65, 5/8W, 2700/3000/4000/6500K, 38°, without cover

Discreet and universal: the UNIVERSAL DOWNLIGHT PHASE recessed light creates targeted lighting thanks to its narrow beam angle of 38 degrees. The IP65 protection class rating means it is protected against dirt and even jets of water. The colour temperature (2700/3000/4000/6500-K) can be selected via the CCT switch before installation. Natural colour reproduction is achieved with a CRI of over 90. And the Quick Connector Box ensures the downlight is quick and easy to install. You can also use the separately available decorative ring, which comes in white, black, gold or chrome.



Tekniske data

Item no.	1007095
IP klasse	IP20/IP65
IK Vandalklasse	IK02
Slagfæsthed	0.2 Joule
Montering	Recessed
Monterings detaljer	Ceiling
Dæmpbar	Ja
Dæmpningstype	trailing edge
Antal lamper ved videresløjfnig	10
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	60/90mA
IP Tæthedsgard	II
Watt	8 W
Min omgivelsetemperatur	-20 °C
Max omgivelsetemperatur	40 °C
Lumen	560/610/680/640 lm
Farvetemperatur	2700/3000/4000/6500 Kelvin
Spredningsvinkel	38 °
Farve	matt black
CRI	90
UGR ≤	28
LXXBXX-data	L70B50

Lyskilde

1370515	A G F
Tilbehør	
1007096	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP65, round, black
1007182	UNIVERSAL DOWN-LIGHT cover , for down-light IP65, square, aluminium
1007183	UNIVERSAL DOWN-LIGHT cover , for down-light IP65, square, gold
1007098	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP65, round, aluminium
1007193	UNIVERSAL DOWN-LIGHT cover , for down-light IP65, square, gold matt
1007181	UNIVERSAL DOWN-LIGHT cover , for down-light IP65, square, white
1007099	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP65, round, gold
1007097	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP65, round, white
1007180	UNIVERSAL DOWN-LIGHT cover , for down-light IP65, square, black
1007192	UNIVERSAL DOWN-LIGHT cover , for down-light IP65, round, gold matt

Højde	4.9 cm
Diameter	8.5 cm
Nettovægt	0.254 kg
Bruttovægt	0.291 kg
Indbygningsdybde	5.5 cm
Installations diameter	6.8 cm
BIG WHITE side	205