



DASAR® 600


recessed floor light, 18W, 3000K, IP65/IP67, square, stainless steel

The square DASAR® recessed floor light is characterised by high quality: in addition to an excellent light output of over 120lm/W, value was also placed on a long lifespan (L80/B10 50,000h) and durability. While the mechanical load of the stainless steel-covered light is 2,000 kg, it is protected from all weather conditions thanks to its IP65/67 rating. The narrow beam of light easily adapts to twilight conditions via the DALI Touch DIM. The robust mounting housing, which is available separately, makes installation both quick and easy.

Tekniske data

Item no.	1007195
IP klasse	IP65/IP67
IK Vandalklasse	IK10
Slagfaste	20 Joule
Montering	Recessed
Monterings detaljer	Ground with Acc.
Dæmpbar	Ja
Dæmpningstype	DALI,Touch
Antal lamper ved videresløjning	28
Mekanisk belastning	2 t
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	550mA
IP Tæthedegrad	I
Watt	18 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	45 °C
Lumen	2200 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	19 °
Farve	matt stainless steel
CRI	80
LXXBXX-data	L80B10

Lyskilde

	
Tilbehør	
1007198	Mounting housing for DASAR® 600

Længde	60 cm
Bredde	10 cm
Dybde	9 cm
Nettovægt	3.874 kg
Bruttovægt	4.767 kg
Indbygnings længde	62 cm
Indbygningsbredde	13 cm
Indbygningsdybde	14 cm
BIG WHITE side	831