



DASAR® 1200

recessed floor light, 34W, 3000K, IP65/IP67, square, stainless steel

The square DASAR® recessed floor light is characterised by high quality: in addition to an excellent light output of over 120lm/W, value was also placed on a long lifespan (L80/B10 50,000h) and durability. While the mechanical load of the stainless steel-covered light is 2,000 kg, it is protected from all weather conditions thanks to its IP65/67 rating. The narrow beam of light easily adapts to twilight conditions via the DALI Touch DIM. The robust mounting housing, which is available separately, makes installation both quick and easy.

Tekniske data

Item no.	1007196
IP klasse	IP65/IP67
IK Vandalklasse	IK10
Slagfasthed	20 Joule
Montering	Recessed
Monterings detaljer	Ground with Acc.
Dæmpbar	Ja
Dæmpningstype	DALI,Touch
Antal lamper ved videresløjfnig	28
Mekanisk belastning	2 t
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	900mA
IP Tæthedsgrad	I
Watt	34 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	45 °C
Lumen	4100 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	19 °
Farve	matt stainless steel
CRI	80
LXXBXX-data	L80B10

Lyskilde

	
Tilbehør	
1007197	Mounting housing for DASAR® 1000

Længde	120 cm
Bredde	10 cm
Dybde	9 cm
Nettovægt	7.415 kg
Bruttovægt	9.019 kg
Indbygnings længde	122 cm
Indbygningsbredde	13 cm
Indbygningsdybde	14 cm
BIG WHITE side	831