




DASAR® XL

round cover 24° 3000K incl. DALI driver stainless steel

The accessible DASAR 2.0 recessed floor light is impressive along its entire length: the linear housing with its round or square cover made of glass and stainless steel is equally stable and of high quality. With its narrow beam angle and warm white light color temperature of 3000 Kelvin, it ensures cosy, uniform outdoor lighting. The CRI value above 80 ensures the most natural color reproduction possible. DASAR is a truly compelling light experience that can be controlled digitally via DALI.;



Tekniske data

Item no.	1007241
IP klasse	IP65/IP67
IK Vandalklasse	IK10
Slagfasthed	20 Joule
Montering	Recessed
Monterings detaljer	Ground with Acc.
Dæmpbar	Ja
Dæmpningstype	DALI,Touch
Antal lamper ved videresløjfning	30
Mekanisk belastning	2 t
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	700mA
IP Tæthedsgrad	I
Watt	27 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	45 °C
Lumen	2790 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	24 °
Farve	matt stainless steel
CRI	80
LXXBXX-data	L80B50

Lyskilde

1807464	
---------	---

Tilbehør

1007246	Mounting housing for DA-SAR 2.0 XL
1007239	Reflector for DASAR 2.0 36°
1007238	Reflector for DASAR 2.0 15°
1007240	Reflector for DASAR 2.0 60°

Dybde	21 cm
Diameter	27 cm
Nettovægt	5.599 kg
Bruttovægt	6.565 kg
Indbygningsdybde	29.5 cm
Installations diameter	28.5 cm
BIG WHITE side	837