




DASAR® XL

square cover 24° 3000 K incl. DALI driver in stainless steel

The accessible DASAR 2.0 recessed floor light is impressive along its entire length: the linear housing with its round or square cover made of glass and stainless steel is equally stable and of high quality. With its narrow beam angle and warm white light color temperature of 3000 Kelvin, it ensures cosy, uniform outdoor lighting. The CRI value above 80 ensures the most natural color reproduction possible. DASAR is a truly compelling light experience that can be controlled digitally via DALI.;



TECHNICAL DATA

Item no.	1007242
IP Code	IP65/IP67
Impact resistance class	IK 10
Impact resistance	20 Joule
Dimmable	Yes
Dimming technology	DALI,Touch
Number of through-wires	30
Mechanical loading	2 t
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	27 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	30
Number of luminaires at LS C16A	30
Level of inrush current	30 A
Duration of inrush current	25 µs
Temperature at glass (light emission)	60 °C
Lumen	2790 lm
Colour temperature	3000 Kelvin
Beam angle	24 °

Light Source

1807464	
---------	---

Accessories

1007246	Mounting housing for DASAR 2.0 XL
1007239	Reflector for DASAR 2.0 36°
1007238	Reflector for DASAR 2.0 15°
1007240	Reflector for DASAR 2.0 60°

Color	stainless steel
CRI	80
Service life	50000 h
Risk Group	1
Length	27 cm
Width	27 cm
Depth	21 cm
Net weight	6.231 kg
Gross weight	7.169 kg
Shape of cut-out	round
Installation depth	29.5 cm
Installation diameter	28.5 cm
BIG WHITE Page	967