DASAR® L

round cover 24° 3000K incl. DALI driver stainless steel

The DASAR 2.0 accessible recessed floor light has a particularly impressive symmetrical appearance. At the same time, the housing with a round or square cover, as preferred, is made of glass and stainless steel and is both stable and of high quality. The beam angle can be selected between 15°36° and 60° with interchangeable reflectors. The generously sized mounting pot makes installation both quick and easy. DASAR is a professional lighting experience that can be controlled digitally via DALI.



Tekniske data

Item no.	1007243
IP klasse	IP65/IP67
IK Vandalklasse	IK10
Slagfasthed	20 Joule
Montering	Recessed
Monterings detaljer	Ground with Acc.
Dæmpbar	Ja
Dæmpningstype	DALI,Touch
Antal lamper ved videresløjfning	45
Mekanisk belastning	2 t
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	500mA
IP Tæthedsgrad	I
Watt	19 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	45 °C
Lumen	1950 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	24 °
Farve	matt stainless steel
CRI	80
LXXBXX-data	L80B50

Lyskilde

1807464	

Tilbehør

1007245	Mounting housing for DA-SAR 2.0
1007239	Reflector for DASAR 2.0 36°
1007238	Reflector for DASAR 2.0 15°
1007240	Reflector for DASAR 2.0 60°

Dybde	18.9 cm
Diameter	20 cm
Nettovægt	3.126 kg
Bruttovægt	3.869 kg
Indbygningsdybde	27.4 cm
Installations diameter	28.5 cm
BIG WHITE side	835