



## Set consisting of 12x 1007090 UNIVERSAL DOWNLIGHT MOVE PHASE IP20 38° and 1007091 UNIVERSAL DOWNLIGHT cover IP20 black R

The UNIVERSAL DOWNLIGHT Multipack contains 12 of the UNIVERSAL DOWNLIGHT MOVE PHASE recessed lights with matching covers in black. An all-round carefree package that makes planning even easier with our UNIVERSAL DOWNLIGHT. The light can be swivelled to direct the beam precisely where you want it to go. The CCT switch allows the color temperature to be selected before installation (2700/3000/4000/6000K), giving you maximum flexibility on the construction site. The choice of total wattage - 5W or 8W - is just as easy. True-to-life colour reproduction is guaranteed thanks to CRI90. The corresponding Quick Connector Box rounds off the overall picture and makes installation of these recessed lights easier than ever.

### Tekniske data

|                                 |                            |
|---------------------------------|----------------------------|
| Item no.                        | 1007273                    |
| IP klasse                       | IP20                       |
| IK Vandalklasse                 | IK02                       |
| Slagfashed                      | 0.2 Joule                  |
| Montering                       | Recessed                   |
| Monterings detaljer             | Ceiling                    |
| Dæmpbar                         | Ja                         |
| Dæmpningstype                   | trailing edge              |
| Antal lamper ved videresløjning | 10                         |
| Primær spænding                 | 220-240V ~50/60Hz          |
| Sekundær strøm / spænding       | 60/90mA                    |
| IP Tæthedsggrad                 | II                         |
| Watt                            | 8 W                        |
| Min omgivelsestemperatur        | -20 °C                     |
| Max omgivelsestemperatur        | 40 °C                      |
| Lumen                           | 560/610/680/640 lm         |
| Farvetemperatur                 | 2700/3000/4000/6500 Kelvin |
| Spredningsvinkel                | 38 °                       |
| Farve                           | matt black                 |
| CRI                             | 90                         |
| UGR ≤                           | 28                         |
| LXXBXX-data                     | L70B50                     |

Lyskilde

|         |                                                                                   |
|---------|-----------------------------------------------------------------------------------|
| 1807465 |  |
|---------|-----------------------------------------------------------------------------------|

|                        |          |
|------------------------|----------|
| Højde                  | 6.1 cm   |
| Diameter               | 8.8 cm   |
| Nettovægt              | 3.124 kg |
| Bruttovægt             | 3.6 kg   |
| Indbygningsdybde       | 7.3 cm   |
| Installations diameter | 6.8 cm   |
| BIG WHITE side         | 209      |