




LID II UP/DOWN

wall-mounted light, 2700/3000K, 28W, PHASE, 100°, anthracite

Adjustable light colour via CCT switch (2700K/3000K), a high colour rendering index of over 80 and a long lifespan of 50,000 hours: the new LID II UP/DOWN wall light emits a powerful light with its upward and downward-facing, pivoting lamp heads which can be adjusted as needed. Simply perfect for atmospheric lighting of pathways, terraces or walls of homes and office buildings.



Tekniske data

Item no.	1007281
Antal lysåbninger	2
IP klasse	IP65
IK Vandalklasse	IK03
Slagfaste	0.2 Joule
Montering	Surface
Monterings detaljer	Wall
Dæmpbar	Ja
Dæmpningstype	trailing edge
Antal lamper ved videresløjfning	20
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	700mA
IP Tæthedegrad	I
Watt	28 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	1500/1500 lm
Farvetemperatur	2700/3000 Kelvin
Spredningsvinkel	100 °
Farve	matt anthracite
CRI	80
LXXBXX-data	L70B20

Lyskilde

1807466	
---------	---

Dybde	6.5 cm
Diameter	22 cm
Nettovægt	0.976 kg
Bruttovægt	1.263 kg
BIG WHITE side	711