




LID II

wall-mounted light, 2700/3000K, 15W, PHASE, 100°, anthracite

Adjustable light colour via CCT switch (2700K/3000K), a colour rendering index of over 80 and a long LED lifespan of 50,000 hours: the new LID II wall light emits a powerful light with its pivoting lamp head which can be adjusted as needed. Simply perfect for atmospheric lighting of pathways, terraces or walls of homes and office buildings.



Tekniske data

Item no.	1007282
IP klasse	IP65
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Montering	Surface
Monterings detaljer	Wall
Dæmpbar	Ja
Dæmpningstype	trailing edge
Antal lamper ved videresløjning	20
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	350mA
IP Tæthedsgard	I
Watt	15 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	800/800 lm
Farvetemperatur	2700/3000 Kelvin
Spredningsvinkel	100 °
Farve	matt anthracite
CRI	80
LXXBXX-data	L70B20
Dybde	6.5 cm

Lyskilde

1807466	
---------	---

Diameter	22 cm
Nettovægt	0.843 kg
Bruttovægt	1.138 kg
BIG WHITE side	711